

*Specialists in
Safety
Identification
Products*

Harris West
5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East
181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Technical Specifications

HAZARD WARNING TAPE

APPLICATION:

Designed expressly for safety marking applications in industrial plants, commercial buildings, institutions and recreational facilities.

Tape fulfills all OSHA requirements. Used to mark obstructions, low hanging objects, pillars, handrails, passageways, aisles and any potentially hazardous areas or objects.

FEATURES / BENEFITS:

- Engineered to hold up under the heaviest most abusive traffic and wear . . . longer than paint!
- Clear embossed protective PVC laminated to a printed PVC layer to give a total backing thickness of 5 mils. Prevents fading and scuffing; provides super abrasion resistance.
- Can be applied quickly and easily; requires minor surface preparation, with no time consuming scraping and cleaning necessary.
- No downtime required for drying after installation.
- Maintenance-free. Original color brilliance is continually renewed by simple wet mopping/washing.
- Conforms with OSHA requirements.

TECHNICAL DATA:

Backing Material:	Polyvinylchloride (PVC) film
Adhesive:	Rubber Based
Total Tape Thickness:	6.0 mils / 0.150 mm
Tensile Strength:	18 lbs. per in. / 3.22 kg per cm
Unwind @ 150 FPM:	65 oz. per in. / 725 gm per cm
Adhesion to steel:	30 oz. per in. / 335 gm per cm
OSHA requirements:	Per paragraph 1910.144 of the Federal Register

Note: The above are typical values and should not be used in writing specifications.