

VINYL PLASTIC TAPE

*Specialists in
Safety
Identification
Products*

APPLICATIONS:

Aisle Marking: Warehouses, hospitals, stages stores; **Selective Masking:** Electroplating, printed circuit boards; **Abrasion Protection:** Bath tubs, spa tubs, aluminum windows; **Color Coding:** Electric and electronic parts, sporting goods, toys. **Decorating:** Furnitures, toys. **Ducting:** HVAC; **Harness Wrapping; Identification; Joint Sealing:** Wrestling Mats; **Sealing Jars:** Solvents, printing inks, and foods.

COLORS AVAILABLE:

OSHA Red, OSHA Yellow, Dark Green, OSHA Light Green, Dark Blue, OSHA Light Blue, Grey, OSHA White and OSHA Black.

Other solid colors are available upon inquiry.

PHYSICAL PROPERTIES:

Backing Material:	Plasticized PVC
Adhesive:	Rubber Base Adhesive
Thickness:	0.15mm
Tensile Strength (N/cm):	23 N/cm
Elongation at Break (%):	150%
Peel Adhesion (N/cm)	1.2N/cm
Unwinding force (N/cm)	2.3N/cm
Temperature Resistance (°C)	-10°C -- + 80°C
Shelf Life (month)	12 months

The manufacturer makes no warranty as to the suitability of the product for buyer's use. Each user of the product should make his own tests to determine the product's suitability for his/its own intended use, and shall assume all risks and liability in connection therewith. The manufacturer's only obligation under its product warranty shall be to replace such quantity of the product as is proved to be defective.

Harris West

5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East

181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162