

Specialists in
Safety
Identification
Products

#### **Harris West**

5181 Argosy Avenue Huntington Beach, CA 92649

> Phone: (714) 898-8048 (800) 222-6866

Fax: (714) 898-7108 (800) 228-1274

### Harris East

181 Conant Drive Pawtucket, RI 02860

> Phone: (401) 727-3160 (800) 443-2821

Fax: (401) 727-3162

## **Technical Specifications**

# **BARRICADE TAPE**

# **Harris BT-Series**

### 4 MIL

# I. SPECIFICATIONS:

Barricade warning tapes will consist of high visibility safety yellow or red polyethylene with bold black letters. Standard letter height is two inches (2"). Tapes help prevent accidents by increasing visibility of hazards and can be tied, stapled or nailed in place.

## II. TEST DATA:

**Material Identification:** Nominal 4 Mil Polyethylene,

3" & 6" wide

**Test Procedure:** ASTM-D-882, Method A

**Specimen Conditions:**  $73^{\circ}\text{F} / 50\% \text{ R.H.}$ 

Test Temperature: 73°F
Elongation: 552%
Tensile Strength (Transverse): 2,100 psi
Tensile Strength (Longitudinal): 2,870 psi
Roll Weight (3" x 1000') 4.5 lbs.