

*Specialists in  
Safety  
Identification  
Products*

**Harris West**  
5181 Argosy Avenue  
Huntington Beach, CA 92649

Phone:  
(714) 898-8048  
(800) 222-6866

Fax:  
(714) 898-7108  
(800) 228-1274

**Harris East**  
181 Conant Drive  
Pawtucket, RI 02860

Phone:  
(401) 727-3160  
(800) 443-2821

Fax:  
(401) 727-3162

Technical Specifications

**DETECTABLE UNDERGROUND TAPE**

**Harris DU-Series**

**I. SPECIFICATIONS:**

Detectable warning tape consists of a nominal 5.5 mil overall thickness, with a solid aluminum foil core. The imprinted warning message is "Buried, or Encased" to prevent ink rub-off, and is impervious to acids, alkalis and other destructive elements found in soil. The imprint is as such that it allows for total reflectivity. A tape must be visibly seen before it can be read.

**II. TEST DATA:**

<b>Material Identification:</b>	5.5 Mil Detectable, 12" wide
<b>Test Procedure:</b>	ASTM-D-882, Method A
<b>Specimen Conditions:</b>	73°F / 50% R.H.
<b>Test Temperature:</b>	73°F
<b>Elongation:</b>	90%
<b>Tensile Strength (Transverse)</b>	5,530 psi
<b>Tensile Strength (Longitudinal)</b>	4,544 psi
<b>Roll Weight - (3" x 1000')</b>	± 7.5 lbs.
<b>Roll Weight - (6" x 1000')</b>	± 15 lbs.

**III. LEGENDS/COLORS & IMPRINTS:**

Caution Buried \_\_\_\_\_ Line Below

(Red or Yellow - Electric), (Yellow - Gas), (Blue - Water), (Green - Sewer), (Orange - Fiber Optic - Telephone - Oil) are some examples. Please see our catalog for a full list.

**IV. LOCATABILITY:**

Harris recommends the use of an industrial grade non-ferrous metal locator utilizing inductive location. The metal mass in the tape is what the locator will pick up so the deeper the burial, the wider the tape should be.

Conductive location is attainable, however, when clipping on to the tape there must be complete contact with the foil. The foil is laminated between 2 layers of plastic making it somewhat difficult to achieve a proper clamp.

Note: Custom Imprinting is available upon request.