

*Specialists in
Safety
Identification
Products*

Technical Specifications

REINFORCED BARRICADE TAPE

Harris BT-R Series

7 MIL

I. SPECIFICATIONS:

Barricade warning tapes will consist of high visibility safety red and/or yellow polypropylene with bold black letters. Standard letter height is two inches (2"). Tapes help prevent accidents by increasing visibility of hazards and can be tied, stapled or nailed in place.

Properties	Especcification:	TOL:	Result:	Method:
Fabric				
Material:	Polypropylene		Polypropylene 100% Virgin	
Color:	Red/Yellow		Red/Yellow	
Warp Count:	10 each/in	+/-0.3 each/in	10 each/in	ASTM D-3775
Weft Count:	8.5 each/in	+/-0.3 each/in	8.5 each/in	ASTM D-3775
Weight:	2.5 oz/yd ²	Min. oz/yd ²	2.53539 Avg. Lbs.	ASTM D-3776
Warp Tensile Strength:	66.14 Lbs.	Min. Lbs.	88.6243 Avg. Lbs.	ASTM D-4632
Weft Tensile Strength:	70.55 Lbs.	Min. Lbs.	76.7196 Avg. Lbs.	ASTM D-4632
Coating:				
Material:	P.E.B.D.+P.P.		P.E.B.D.+P.P. 100% Virgin (Profax)	
Color:	Natural		Natural	Visual
Weight:	0.796 oz/yd ²	+/-0.3 oz/yd ²	0.6317 Avg. oz/yd ²	ASTM D-3776
Packaging:				
		Roll & Cover	OK	

Notes:

Free Humidity Storage Place and No presence of Oxidant Agents (NO₂, SO₂, H₂S).
No Storage in Darkness.
Move the material each 3 months maximum.

Harris West

5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East

181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162