

*Specialists in
Safety
Identification
Products*

Harris West
5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East
181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Technical Specifications

BARRICADE TAPE

Harris BT-R Series

5 MIL

I. SPECIFICATIONS:

Barricade warning tapes will consist of high visibility safety yellow or red polypropylene with bold black letters. Standard letter height is two inches (2"). Tapes help prevent accidents by increasing visibility of hazards and can be tied, stapled or nailed in place.

Construction:	8 x 3 Tape
Coating Thickness:	1.5 mils each side (+/- 10%)
Weight:	3.1 oz/Sq. yd. (+/- 10%)(ASTM D-1910)
Tensile Strength:	90lbs warp x 60lbs weft (ASTMD-751, Grab)
Tear Strength:	31lbs warp x 18lbs weft (ASTMD-751, Tongue)
Thickness:	5.0 Mils (+/- 10%)

These are typical property values and are intended as guides only. The figures listed do no represent specifications limits.