

*Specialists in
Safety
Identification
Products*

Harris West
5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East
181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Technical Specifications

**RADIATION
HAZARD WARNING TAPE**

#RT230YM

APPLICATION:

A high-strength cloth tape that effectively combines economy with performance!

A quality matte surface backing and positive-seal adhesive make for a truly "full value" general-purpose tape. Ideally suited for a wide range of holding, sealing, splicing and decorative applications. In addition, the yellow and magenta stripe with radiation symbol make it ideal for use in nuclear facilities.

FEATURES / BENEFITS:

- Offers a quality construction . . . yet is economically priced.
- Superior adhesion, with clean removal when needed.
- Highly conformable to irregular surfaces and odd shapes.
- Provides a positive dust and dirt resistant seal.
- Controlled unwind for quick, easy tape application.
- Hand tearable - no need for knife, scissors or dispenser.
- Meets government specifications A-A-1586A and PPP-T-60E

TECHNICAL DATA:

Backing Material:	Vinyl-coated cotton cloth
Adhesive:	Synthetic rubber/resin
Colors:	Yellow and Magenta w/radiation symbol
Total Tape Thickness:	12.0 mils / 0.305 mm
Tensile Strength:	45 lbs. per in. / 8.0 kg per cm
Adhesion to Steel:	60 oz. per in. / 670 gm per cm
Unwind @ 150 FPM	25 oz. per in. / 280 gm per cm
Government Specification:	A-A-1586A and PPP-T-60E

Note: The above are typical values and should not be used in writing specifications.

STOCK SIZE:

2" x 30 yards