

*Specialists in
Safety
Identification
Products*

Technical Specifications

UNDERGROUND TAPE

Harris UT-Series

I. SPECIFICATIONS:

Non-Detectable warning tape for the protection, location and identification of underground utility installations. Consists of a nominal 4.0 mil overall thickness inert plastic film formulated to resist degradation due to acid and alkalies found in soils. Product is also lead free.

II. TEST DATA:

| | |
|---|---|
| Material Identification: | 4 Mil Polyethylene, 3", 4" & 6" wide |
| Test Procedure: | ASTM-D-882, Method A |
| Specimen Conditions: | 73°F / 50% R.H. |
| Test Temperature: | 73°F |
| Elongation: | 552% |
| Tensile Strength (Transverse): | 2,100 psi |
| Tensile Strength (Longitudinal): | 2,870 psi |
| Roll Weight (3" x 1000') | 6 lbs. |
| (6" x 1000') | 12 lbs. |

Harris West

5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East

181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162