

Specialists in Safety Identification Products

Harris West

5181 Argosy Avenue Huntington Beach, CA 92649

> Phone: (714) 898-8048 (800) 222-6866

Fax: (714) 898-7108 (800) 228-1274

Harris East

181 Conant Drive Pawtucket, RI 02860

> Phone: (401) 727-3160 (800) 443-2821

> Fax: (401) 727-3162

Technical Specifications

ELECTRICAL TAPE

Black, Blue, Gray, Green, Red, White, Yellow, Orange, Purple, Brown

SPECIFICATIONS:

Typical Applications:

Used for insulating, protection and color coding of electrical wire; for wire harnessing in automotive industry.

Thickness:

Physical Properties Elongation: Tensile Strength: Peel Adhesion (N/cm): Voltage Breakdown: Flame Retardance: Temperature Resistance (°C): Shelf Life (months)

Construction Backing: Adhesive:

Certifications:

200% 26N/cm 1.8N/cm 8kv Flame Retardant -10°C -- +80°C 12 Months

7 Mil/0.18mm

Plasticized PVC Rubber Based Adhesive

CE, CSA, UL

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.